## STRATA BLADE 4K6052 – MONO BASIN MIXER

## FRANCIS KITCHEN&BATHROOM

				Specification				
			Finish	Chrome				
				Body	Bra	ISS		
				Fittings Metal plate, washer, stu & locking nut			er, stud	
				Connection M12 – DN8 flexible hoses with ½" BSP threaded ends				
				Min dynamic pressure			•	0.1
				Max dynamic pressure			е	6
- 167				Max static pressure				16
			Max water temperature			e	60°C	
					Flow	/ rates	;	
	23			Pressure	0.1	0.5	1	3
	40 MAX		33	Aerator	1	2.3	3.4	3.6
Ø 50.		125		F/Straight	1.1	5.9	9.3	17.5
				All Pressures in Bar. All flow in L/Min. Dimensions supplied are nominal and subject to tolerance.				
				Inclusion or restrictors (sold separately unless stated) will affect flow rate result.				
				Performance details are based on trials under test conditions and for guidance only.				
				The Company reserves the right to change product specification without prior notice.				
Features & Benefits				Certifications				
<b>10</b> <b>YEAR</b> Guarantee	Low Pressure	Flexible Hose	Click Waste	<b>6</b> 5.3			kiwa approve Wkwater Regulation	14
				Tested at 0	.2 bar	2210	773 – 0	ct 27
		Į.						
Flow Straightener	Eco Aerator	Single Flow						

**Sth** Westco Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT