STRATA BLADE

4K6057 - WALL MOUNTED BATH FILLER KITCHEN&BATHROOM

FRANCIS

				Specification					
				Finish	Ch	Chrome			
				Body	Bra	Brass			
Pëgler			Fittings	N/A	N/A				
			Connection	1⁄2"	¹ ⁄ ₂ " BSP Threaded tail				
				Min dynamic pressure			1		
				Max dynamic pressure			e	6	
- 230)	Max st	atic pre	ic pressure		16	
				Max wat	perature		60°C		
					Flow rates				
<u> </u>		ľ U	191	Pressure	0.1	0.5	1	3	
		-	-	Aerator					
	45~57 12 MAX			F/Straight	2.6	10.5	15.4	28.1	
				All Pressures in Bar. All flow in L/Min. Dimensions supplied are nominal and subject to tolerance.					
	4				Inclusion or restrictors (sold separately unless stated) will affect flow rate result.				
					Performance details are based on trials under test conditions and for guidance only.				
					The Company reserves the right to change product specification without prior notice.				
	Certifications								
10 YEAR Guarantee	High Pressure	Flow Straightener	Single Flow	♦ 28 I/I Tested at 5					
		I	I						

Sth Westco Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT